



Draft DDO43 – Bridge Road Central

Information Sheet



Bridge Road Central is located on north side of Bridge Road between Church Street and Gardner Street. It is the civic and community heart of Bridge Road Activity Centre, anchored by the Richmond Town Hall and close to Citizens Park, the two high schools and other community and recreation facilities. It contains a mix of commercial, retail and residential uses, clusters of heritage buildings and some larger development sites.

Within the precinct, Gleadell Street and Griffiths Street provide important links between Bridge Road and the precinct's civic and community facilities.



What is this Design and Development Overlay trying to achieve?

Draft Design and Development Overlay – Schedule 43 (Draft DDO43) generally supports lower mid-rise development up to 5 storeys along Bridge Road so that the local landmarks and the clusters of heritage buildings remain visually prominent.

It also supports areas of high quality taller development on the larger sites on the north side of Bridge Road up to 7 to 8 storeys.

The DDO requires the heritage street wall / streetscape to be retained. New or infill buildings need to match this 2 to 3 storey height. Any development above the heritage building should be pushed back by at least 6 metres.

It requires that key views to across the precinct from Citizens Park and the corner of Bridge Road and Church Street to the iconic Richmond landmarks, the Richmond Town Hall and St Ignatius' spire and belfry are maintained.

Under the DDO, development should be designed to create safe, active and attractive street frontages.

Development must be designed to make sure buildings retain sunlight to important footpaths along Church Street, Gleadell Street, Griffiths Street, Coppin Street and the southern side of Bridge Road.

It also aims to make sure new development minimises its amenity impacts on the low scale residential neighbourhoods which abut the Precinct. This includes minimising overlooking, overshadowing and visual bulk.

More information

If you would like to know more about this project, contact us on 9205 5555 or strategicplanning@yarracity.vic.gov.au

What are the main design requirements to guide potential developments?

Below are maps and tables providing a summary of built form and design requirements in draft DDO43 (see Section 2.2 of the DDO43).

Built form and design requirements in DDO43 relate to front setbacks, street wall height, setbacks for upper levels, building height and transition of potential development towards residential properties at the rear.

The DDO also includes requirements and guidelines on overshadowing, facade design, access and movement and others.

NOTE: Amendment C291yara also includes new policy which describes the proposed future character of the precinct (see [Clause 21.11 – Local Areas](#)).

Mandatory and preferred requirements

DDO43 includes a mix of mandatory and preferred requirements.

A mandatory requirement is a requirement or control that must be met. There is no opportunity to vary it. For example, a proposal cannot be approved taller than the mandatory height listed in the DDO.

A preferred requirement provides for flexibility in the approach to achieve the required outcome.

(See the [Design and Development Overlays Information Sheet](#) for more information about how DDOs work.)

Building heights and interfaces

The Height and Interface Plan and Interface Table show the maximum building heights and the interface requirements that apply.

Mandatory maximum heights are shown with cross hatching.


See *Section 2.2 Building Height, Street Wall and Setback and Upper Level Requirements* in draft DDO43 for greater detail.

NOTE

This information sheet provides a summary of some requirements and where they apply can be found in the DDO. It is not part of the formal amendment documentation. It is recommended you refer to the DDO and the supporting documents below if you wish to make a submission. Go to the Yarra website to review [Draft DDO43](#).

Common terms

Street wall, upper level setbacks and overall building height are terms that are used in the DDO which set the general building envelop which new buildings or additions should fit into (see the diagram below).




1. Street wall
2. Upper level setback
3. Overall building height
4. Residential interface

Source: Johnston Street Local Area Plan - Built Form Analysis and Recommendations (December 2015)

Heritage buildings are buildings within a Heritage Overlay in the planning scheme, which are graded as either 'Contributory' or 'Individually Significant' or any building on the Victorian Heritage Register.

Building Heights and Interfaces



Legend

Precinct Boundary

Green Streets - Key pedestrian/cycle routes

Note all heights are preferred maximum building Heights except where mandatory maximum building heights are shown

Building Heights

- 11m
- 15m
- 18m
- 24m
- 28m
- Mandatory heights
- Limited development potential

Street wall height and setback interface ref

- Interface A
- Interface B
- Interface C
- Interface H Residential interface (laneway)
- Interface I
- 2m Setback

Interfaces

Interface Type	Street Wall Height	Street Wall Setback	Upper Level Setback
Interface A 	Retain existing street wall height for heritage buildings 8m-11m (2-3 storeys) for other buildings <u>Mandatory</u> Other buildings should match the parapet height of the adjoining heritage building, for a minimum length of 6m from the heritage building. <u>Preferred</u>	Retain existing street wall setback for heritage buildings <u>Mandatory</u> 0m for other buildings <u>Preferred</u>	6m minimum <u>Mandatory</u> For buildings >15m (4 storeys), the uppermost level should be set back 9m minimum <u>Preferred</u>
Interface B 	Retain existing street wall height for heritage buildings 8m-11m (2-3 storeys) for other buildings <u>Mandatory</u> Other buildings should match the parapet height of the adjoining heritage building, for a minimum length of 6m from the heritage building <u>Preferred</u>	Retain existing street wall setback for heritage buildings <u>Mandatory</u> 0m for other buildings <u>Preferred</u>	13m minimum <u>Preferred</u>
Interface C 	Retain existing street wall height for heritage buildings 8m-11m (2-3 storeys) for other buildings Match the parapet height of the adjoining heritage building, for a minimum length of 6m from the heritage building. <u>Preferred</u>	Retain existing street wall setback for heritage buildings. Elsewhere - 0m <u>Preferred</u>	6m minimum <u>Preferred</u>
Interface I 	11m (3 storeys) maximum <u>Preferred</u> NOTE: Interface I control relates to side / rear wall height rather than street wall height	17 Gleadell Street – 2m minimum setback to the southern boundary <u>Preferred</u> NOTE: Interface I control relates to side / rear wall setback rather than street wall setback	Minimum 4.5m from the centre of the laneway <u>Preferred</u>

Access and Movement

Vehicle access

The requirements aim to provide a safe and accessible environment for everyone and to limit potential conflict between vehicle movements and pedestrians. See *Section 2.2 Vehicle Access* in draft DDO43 for more information.



Pedestrian and Bicycle Access

The DDO requires new development consider the design of bicycle parking and how pedestrians and cyclists safely and easily access the building. See *Section 2.2 Pedestrian and Bicycle Access* in DDO43 for more information.

What are some of the other design requirements?

Views to landmarks

Views to landmarks are an important aspect of the Bridge Road Activity Centre. The DDO identifies the following landmarks:

1. Richmond Town Hall Clock Tower; and
2. St Ignatius Church Spire and tower belfry.

New buildings must not obstruct views to these landmarks.

See *Section 2.2 View Lines* in DDO43 for all the details. The viewlines are shown in Plan 1 in DDO43.

Interfaces to residential properties

The DDO includes a requirement which ensure new buildings minimise any impacts on the amenity of adjoining low scale residential neighbourhoods such as overlooking or reducing sunlight to backyards.

See *Section 2.2 Interface to residential properties in NRZ or GRZ requirements* in DDO43 for all the details.

Building separation

Building separation refers to the space between buildings at upper levels. The requirement aims to ensure good levels of internal amenity for current and future building occupants and provides a visual break between taller buildings.

See *Section 2.2 Building Separation* in DDO43 for all the details.

Overshadowing

The requirement aims to retain sunlight to the southern footpath on Bridge Road and identified Green Streets ie important pedestrian and cycle routes and are shown on Height and Interface Plan in this Information Sheet and in the DDO).

See *Section 2.2 Overshadowing* in DDO43 for all the details.

Design quality

The DDO includes a number of requirements to ensure buildings are well designed.

Several requirements ensure new development provides high quality and pedestrian focussed design at street level. They will ensure the precinct's main streets are activated. Where existing heritage buildings are not a constraint, the DDOs also encourage generous entry spaces to buildings where there are narrow footpaths. New designs need to be designed to fit into the character of the area.

The DDO also addresses how new development responds to heritage and design details like services on roof and front of buildings (like meter boxes and gas mains).

Developments along identified Green Streets (shown on Height and Interface Plan in this Information Sheet and DDO43) are encouraged to contribute to urban greening through planting, including vertical and rooftop gardens.

See Section 2.2 Design Quality in DDO43 for all the details.

How to make a submission?

Submissions must be made in writing. Submissions close **27 October 2021**.

- **Email:** strategicplanning@yarracity.vic.gov.au
- **Post:** Attention Strategic Planning PO Box 168, Richmond VIC 3121
- Subject line: Amendment C291yara - Submission

Note: Your submission must indicate if you support or oppose the draft amendment (or parts of it) and outline any recommended changes to the draft amendment.

If you do not receive a confirmation email on your submission, please get in touch with us on 9205 5555.

National Relay Service

TTY 133 677 then (03) 9205 5055

Languages

العربية 9280 1930

中文 9280 1937

Ελληνικά 9280 1934

Italiano 9280 1931

Español 9280 1935

Tiếng Việt 9280 1939

Other 9280 1940