



GENERAL NOTES

1. BLUESTONE BLOCKS (PITCHERS) ARE NOMINALLY 300x255x150mm.
2. PITCHER KERB TO BE LAID IN STRETCHER BOND PATTERN.
3. THIS DRAWING TO BE READ IN CONJUNCTION WITH COUNCIL SPECIFICATION "CONSTRUCTION OF PITCHER KERB AND CHANNEL AND PRAM CROSSINGS".
4. DAMAGED AND UNSUITABLE PITCHERS TO BE REPLACED.
5. INVERT TO BE FINISHED TO GRADE WITH WOODEN FLOAT. INVERT JOINT TO BE NOM. 35mm, OTHER JOINTS TO BE NOM. 15mm
6. CEMENT TREATED CRUSHED ROCK BEDDING BELOW THE CHANNEL SHALL HAVE A MINIMUM COMPACTED DENSITY OF 90% OF THE MODIFIED AASHO VALUE. CEMENT TREATED CRUSHED ROCK IN FRONT OF THE CHANNEL SHALL HAVE A MINIMUM COMPACTED DENSITY OF 95% OF THE MODIFIED AASHO VALUE.

Yarra Standard: YSD306 Drawing Title:

PITCHER KERB & TWO PITCHER CHANNEL

Scale at A4 N.T.S

REV	DATE	DRAWN BY
A	29/11/07	HL
B	30/04/12	DKC
C	04/10/13	OK

