



PLAN



SECTION B-B

>166 DEGREES  
FOR DISABILITY ACCESS

NO BULLNOSE



SECTION A-A

**GENERAL NOTES**

1. INVERT TO BE FINISHED TO GRADE WITH WOODEN FLOAT.  
INVERT JOINT TO BE NOM.35mm, OTHER JOINTS TO BE NOM 15mm.
2. BLUESTONES WITHIN THE PRAM CROSSING ARE TO BE SLICED IN HALF AND INVERTED SMOOTH SIDE UP.
3. THIS DRAWING IS TO BE READ IN CONJUNCTION WITH COUNCIL'S SPECIFICATIONS SECTION H-H " CONSTRUCTION OF BLUESTONE KERBS, CHANNELS AND PRAM CROSSINGS.
4. CEMENT SLURRY TO BE FLUSH WITH BLUESTONE PITCHER SURFACE.
5. REFER STANDARD DRAWING YSD401 FOR ASPHALT AND CONCRETE FOOTPATH DETAILS.
6. REFER STANDARD DRAWING YSD402 FOR ASPHALT FOOTPATH DETAILS IN SHOPPING STRIP.

**Yarra Standard: YSD403**

**Drawing Title:**

BLUESTONE KERB LAYBACK PRAM CROSSING

Scale at A4 N.T.S

REV	DATE	DRAWN BY
A	28/11/07	HL
B	30/04/12	DKC
C	08/04/16	HL

